

## FOMBLIN® Y-LVAC 16/6

### SECTION I - CHEMICAL PRODUCTS AND COMPANY IDENTIFICATION

Ausimont USA, Incorporated  
10 Leonards Lane  
Thorofare, New Jersey 08086  
Main telephone: 609-853-8119

#### EMERGENCY TELEPHONE NUMBERS:

CHEMTREC: 800 - 424 - 9300  
Ausimont USA: 609 - 251 - 3467

#### Product Names:

FOMBLIN(R) Y-LVAC 16/6

#### Chemical Name:

Propene, 1,1,2,3,3,3-hexafluoro, oxidized,  
polymerized

#### CAS Number:

69991-67-9

#### Chemical Family:

Fluorocarbons, Perfluorinated polyethers

#### EMERGENCY OVERVIEW.

**Clear, colorless liquid. Thermal decomposition will generate hydrogen fluoride (HF), which is corrosive.**

### SECTION 2 - COMPOSITIONAL INFORMATION

<u>Name:</u>	<u>CAS:</u>	<u>Approximate Weight</u> <u>(% wt.):</u>
Propene, 1,1,2,3,3,3-hexafluoro, oxidized, polymerized	69991-67-9	100

### SECTION 3 - POTENTIAL HEALTH EFFECTS

#### Effects of Overexposure:

Eye Contact:

Eye contact may cause slight irritation.

Skin Contact:

Skin contact may cause slight irritation.

Inhalation:

Inhalation of vapors or mists may cause respiratory tract irritation.

Ingestion:

Ingestion may cause nausea and vomiting.

### SECTION 4 - FIRST AID MEASURES

Eye Contact:

Flush eyes for 15 minutes with large amounts of water, while keeping the eyelids open. Seek medical

Skin Contact:	attention if irritation persists. Wash skin thoroughly with mild soap and water. Flush with lukewarm water for 15 minutes. Seek medical attention if irritation persists.
Inhalation: mouth	Remove victim from contaminated area. Give -to-mouthbreathing and/or CPR, if needed. Oxygen Can be given under doctor's orders.
Ingestion:	If victim is conscious, have them drink three to four ounce glasses of water or milk. Do not induce vomiting. Call a physician or the poison control center. If victim is unconscious, have an ambulance immediately take them to a hospital. Do not give anything by mouth to an unconscious person.
Note to physician:	None.

### **SECTION 5 - FIRE FIGHTING MEASURES**

Flash Point:	None.
Lower Flammable Limit:	Not available.
Upper Flammable Limit:	Not available.
Auto ignition:	Not available.
Extinguishing Media:	Water (spray or fog), foam, carbon dioxide (CO2), Or dry chemical.
Unusual Fire Hazards:	Fluoropolymer materials will degrade upon Prolonged heating or in a fire, liberating carbonyl fluoride and hydrogen fluoride (HF). HF gas is toxic if inhaled or it comes into contact with moist skin. HF has an ACGIH TLV ceiling value of 3 ppm (2.6 mg/m3) and an OSHA PEL TWA of 3 ppm. Carbonyl fluoride has an ACGIHTLV TWA and OSHA PEL TWA of 2 ppm (5 mg/m3).
Firefighting Procedures:	Use self-contained breathing apparatus (SCBA) and skin protection for acid gas exposure. Do not enter fire area without proper protection. Fight fire from safe distance. If possible, air monitoring should be performed.

### **SECTION 6 -ACCIDENTAL RELEASE MEASURES**

Releases:	In case of a release or spill, absorb material onto vermiculite or similar inert absorbent. Use
Ausimont	Perfluorosolv(TM) PFS-1 as an aid in cleaning up Any residual fluid. Place spilled material into covered container for disposal. Dispose of according to applicable local, state and federal regulations. Extinguish all ignition sources and evacuate the area. Exercise caution; spill area my be slippery.

## **SECTION 7 - HANDLING AND STORAGE**

Use the recommended personal protective equipment. Do not eat, drink, smoke or apply make-up when using this material. Wash hands after using this material and before entering non-work areas or handling food or applying cosmetics. Do not use tobacco products in the immediate area.

Store in a cool area keeping material packaged in original containers and tightly closed. Keep away from heat, sparks and flames. Do not store near combustible materials.

## **SECTION 8 - EXPOSURE CONTROLS/PERSONAL PROTECTION**

ACGIH Threshold Limit Value

(8 hr. time weighted average): None established.

OSHA Permissible Exposure Limit

(8 hr. time weighted average): None established.

### **ENGINEERING CONTROLS:**

Ventilation Requirements:

Local exhaust: vent vapors or mists generated by processing away from operating personnel. Local exhaust ventilation should be at a rate of 50 feet per minute.

### **PERSONAL PROTECTIVE EQUIPMENT:**

Respiratory Protection:

No occupational exposure standards have been developed for this material. In situations where exposure to vapors or mists is likely, NIOSH/MSHA approved respirators equipped with organic filter cartridges are recommended. Respirator use limitation made by NIOSH/MSHA or the respirator manufacturer must be observed. Respiratory protection program must be in accordance with 29 CFR 1910.134.

Eye and face protection:

ANSI Z.87 approved safety glasses with side shields or equivalent chemical splash goggles.

Skin protection:

Rubber or latex gloves are recommended.

## **SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES**

Appearance:

Clear liquid.

Color:

Colorless.

Odor:

Odorless.

pH:

Not applicable

Vapor pressure:

Less than JOA -3 torr at 20 degrees C.

Vapor density:

Not available.

Boiling point:

Greater than 270 degrees C.

Melting point:

Not available.

Specific gravity:

1.7- 1.9.

Solubility in water:

Insoluble.

## **SECTION 10 - STABILITY AND REACTIVITY**

Stability:	This material is stable.
Reactivity:	This material is not reactive.
Conditions to avoid:	Avoid contact with heat, sparks, flames, other Ignition sources, or heating above 290 degrees C (554 degrees F).
<b>Incompatibility/materials to avoid:</b>	Strong or non-aqueous alkali Lewis acids above 100 degrees C (212 degrees F). Alkali metals and halogenated compounds.
<b>Hazardous decomposition products:</b> generate	Thermal decomposition of this product will  hydrogen fluoride (HF), which is corrosive, causing burns on contact with skin and other tissue.

## **SECTION 11 - TOXICOLOGY INFORMATION**

Rat oral LD50:	Greater than 25.65 gms/kg.
Rat intraperitoneal LD50:	Greater than 25 gms/kg.
Rat dermal LD50:	Greater than 2 gms/kg.
Rabbit skin irritation:	Non irritating.
Rabbit eye irritation:	Non irritating.
Guinea pig sensitization:	Not a sensitizer.

## **SECTION.12 - ECOTOXICOLOGICAL INFORMATION**

No ecotoxicological information is available for this material.

## **SECTION 13 - DISPOSAL INFORMATION**

Waste disposal: Material, as supplied, is a hazardous waste. Incinerate in a high-temperature incinerator designed to burn fluorine-containing materials. Processing, use or contamination may make this information inaccurate or incomplete.

## **SECTION 14 - TRANSPORTATION INFORMATION**

Shipping class: Not regulated by DOT.

## **SECTION 15 - REGULATORY INFORMATION**

This product is listed on the Toxic Substance Control Act (TSCA) Section 8(b) Chemical Inventory and the Canadian Environmental Protection Act (CEPA) provisional domestic substances list (DSL).

This product is not a "hazardous substance" as defined by OSHA Hazard Communication Standard, 29 CFR 1910.1200.

This product is not a "controlled product" as defined by the Canadian Workplace Hazardous Materials Information System (WHMIS).

SARA Section 302 Extremely Hazardous Substances list - not listed.

SARA Section 311/312:

Acute:	No.
Chronic:	No.
Fire:	No.
Reactivity:	No.
Sudden Release of Pressure:	No.
NFPA Ratings (scale of 0 - 4):	
Health:	I
Fire:	0
Reactivity:	0

## **SECTION 16 - OTHER**

ORIGINAL ISSUE:	10/89
DATE REVISED:	08/04/95
REVISION NUMBER:	3
REASON FOR REVISION:	Changed address, telephone numbers
PREPARED BY:	Barry R. Weissman, REM, CSP, CHMM
FILE REFERENCE:	\MSDS\FOMBLIN\LVAC16-6

The above information is accurate to the best of our knowledge. However, since data, safety standards and governmental regulations are subject to change and the conditions of handling and use, or misuse are beyond our control, AUSIMONT makes no warranty, either expressed or implied, with respect to the completeness or continuing accuracy of the information contained herein and disclaims all liability for reliance thereon. User should satisfy themselves that they have all the current data relevant to a particular use.